


## **Grafham Plug & Play Emergency Pack**





#### **General data**

| Symbols                     | IP   IK   UKCA   CE  Class   Weee     |
|-----------------------------|---------------------------------------|
| Install Connector Type      | Flying Lead                           |
| Input Cable                 | 1.5M H05RN-F 4-Core                   |
| Input Electrical Connection | Live   Neutral   Earth   P Live       |
| General Application         | Commercial   Industrial   Educational |
| Operating Temperature Range | 0 - +30 °C                            |
| Warranty                    | 5 Years                               |
|                             |                                       |

### **Optical data**

Photobiological Risk Group RG0

#### **Electrical data**

| Wattage +/-10%          | 4 W         |
|-------------------------|-------------|
| Total power consumption | 4 W         |
| Mains voltage           | 220 - 240 V |
| Lamp power factor       | 0.5         |
| Electrical protection   | Class I     |
| Driver Output           | 20 -24 V    |
| Nominal Frequency       | 50/60 Hz    |

## **Emergency data**

| LiFeP04        |
|----------------|
| 3600mAh        |
| 2 Year         |
| 24 Hours       |
| Non-Maintained |
| Manual         |
| 3 Hours        |
|                |

# **Physical Data**

| Housing Colour | Black RAL9005 |  |
|----------------|---------------|--|
| Body Material  | Polycarbonate |  |
| Driver Housing | Polycarbonate |  |

| IP Rating              | 40 IP   |
|------------------------|---------|
| IK Rating              | 8 IK    |
| Nominal Product Length | 200 mm  |
| Nominal Product Width  | 200 mm  |
| Nominal Product Height | 36 mm   |
| Weight                 | 0.65 kg |

## **Packaging**

| Single Packaging type   | Carton / Inner |
|-------------------------|----------------|
| Product EAN number      | 5055379558060  |
| Packaging Inner Length  | 220 mm         |
| Packaging Inner Width   | 215 mm         |
| Packaging Inner Height  | 95 mm          |
| Single packaging weight | 0.9            |

# **Standards and Approvals**

| Manufactured In Accordance To | EN 60598-1 EN6058-2-22 |
|-------------------------------|------------------------|
| CE Mark                       | YES                    |
| UKCA Mark                     | YES                    |
| WEEE Symbol                   | YES                    |
| Certificate of Conformity     | Available on Request   |
| Accredited Members            | LIA, ISO9001           |

#### Media

| PDF Datasheet      | YES |
|--------------------|-----|
| LDT File           | NO  |
| Image              | YES |
| Product Label      | YES |
| Instruction Manual | YES |
| Packaging          | YES |