Ei146e

Optical Smoke Alarm



- Optical sensor quick response to slow smouldering fires
- Automatic dust compensation
- Mains powered with 9V Alkaline battery back-up
- Easi-fit base for quick and simple installation
- Kitemarked to BS EN14604:2005
- 5 year guarantee















Description

The Eil46e Optical Smoke Alarm is a mains powered alarm with a 9V Alkaline battery back-up and contains a proven optical smoke chamber. The alarm features a new modern design and improved optical sensor with sealed insect mesh and automatic dust compensation for reduced false alarms. It is supplied with an easi-fit base to make it quick and simple to install. Compatible with the Eil68RC RadioLINK Base for wireless interconnection

Technical

Sensor Type	Optical	Indicators	Green - Power / Red - Alarm or fault
Supply Voltage (V)	230	Voltage Type	AC
Battery Type	Alkaline PP3	Power Consumption (W)	0.75

Dimensions & Weights

Depth (mm)	50	Height (mm)	148
Width (mm)	148	Product weight (kg)	0.345

Packaged weight (kg) 0.389

Approvals & Warranty

Certification/Approvals	BS EN 14604:2005	Warranty	5 year warranty
EAN Number	5099383010206		

Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

an **Êi** Company