

Technical Specification



Product Code: VPSC536BK **Description:** 13A Ingot 2 Gang Double Pole Switched Socket Outlet





Insert & Housing: Urea

Earth Strap: Mild Steel

Frequency (Hz) 50

Contacts: Silver "on-lay" Copper / Brass

Terminals: Brass

Terminal Torque Value (Nm) 2

General Information

Plate Dimensions (mm) 146 (W) x 88 (H) x 8 (D) Dimensions With Gasket (mm) 149 (W) x 91 (H) x 9 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Victorian Finish Satin Chrome

Insert Colour Black Gasket Colour Black

> Materials Front Plate: Stainless Steel

> > Switch Cover: Stainless Steel

Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass

Gasket: Nylon

Anti Microbial Certified No

Rated Voltage (V~) (Ue) 250

Resistive Load Rating (A) 13 Termination Type Screw

Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Double Pole Switch Yes Twin Earth Terminals Yes

Minimum Back Box Depth (mm) 25

Ingress Protection IP20

Operational Temperature (°C) -5 to +40

Warranty (Years)

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit

diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

